



KTLC-17NA (black or beige) 17" LCD Touch Monitor Specifications:

Monitor Specifications		Touch Screen specifications	
Size	17"	Technology	Resistive
View Area	17"	Material	Plastic on Glass
Display Type	Color TFT	Surface Treatment	Anti-glare hard coating
Brightness (cd/m2)	250	Spacer	Invisible (patented)
Contrast Ratio	450:1	Light Transmission	80% nominal
Horizontal Viewing Angle	160 degrees	Scratch Resistance	3H pencil hardness min.
Vertical Viewing Angle	145 degrees	Touch Resolution	2048 x 2048
Video Signal	Analog	Interface Controller	External box, USB or Com port.
Horizontal Scan	31.5-81KHz	Controller Size (mm)	76.2 x 38.1 x19
Vertical Scan	56-75Hz	Power	5 VDC direct from computer.
Max. Resolution (PC)	1280 x 1024	Operating Systems	Windows 95, 98, NT, ME, 2000, XP, Mac, Linux.
VESA Mounting Holes	100 x 100 mm	Drivers	Mouse emulation (click/drag)
Response Time	16 ms	Activation Force	50-120 grams per square cm
Display Area (mm)	337.9x 270.3	Response Time	< 0.1 sec.
Colors	16.7M	Position Accuracy	3 mm maximum error
Power (VAC)	100-240V, 50-60Hz	Touch Mode	Mouse click/drag functions
Power Consumption	30W maximum	Operating Temperature	-10 to 70 degrees C
Operating Temperature	5 to 35 degrees C	Storage Temperature	-30 to 85 degrees C
Storage Temperature	-10 to 60 degrees C	Humidity	95%RH @ 40C for 96 hours
Speakers	No	Chemical Resistance	Resist to all cleaning chemicals
USB hub	No	Durability	3 million touches each point
Dimensions (mm) WxHxD	375.4 x 326.5 x 61 Without stand		
Weight (KGs)	4.6		
Warranty	3-year Parts & Labor	Warranty	1-year parts/labor +2-year labor only for touch screen. 3-year parts/labor for controller.

Lifetime free drivers upgrade and technical support.

KEYTEC'S product is the "Best Buy" in touch screen industry.